Yellow Card[™]

File Number: E123529

Sumika Polycarbonate Limited

Technical Service & Development Lab 1-98 Kasugade Naka 3-Chome Konohana-Ku, Osaka 554-8558 Japan

FD5071L-C7

Polycarbonate (PC), pellets



Flame Rating UL 94 IEC 60695-11-10, -20 1.0 mm, ALL V-0 Thermal Value Test Method RTI Elec UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C 3.0 mm 80.0 °C	Flammability	Value	Test Method
3.0 mm, ALL 3.0 mm, ALL V-0 Thermal Value Test Method RTI Elec UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	Flame Rating		
Thermal Value Test Method RTI Elec UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	1.0 mm, ALL	V-1	IEC 60695-11-10, -20
RTI Elec UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	3.0 mm, ALL	V-0	
1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	Thermal	Value	Test Method
3.0 mm 80.0 °C RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	RTI Elec		UL 746B
RTI Imp UL 746B 1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	1.0 mm	80.0°C	
1.0 mm 80.0 °C 3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	3.0 mm	80.0°C	
3.0 mm 80.0 °C RTI Str UL 746B 1.0 mm 80.0 °C	RTI Imp		UL 746B
RTI Str UL 746B 1.0 mm 80.0 °C	1.0 mm	80.0°C	
1.0 mm 80.0 °C	3.0 mm	80.0°C	
	RTI Str		UL 746B
3.0 mm 80.0 °C	1.0 mm	80.0°C	
	3.0 mm	80.0°C	

Page 1 of 1 Form Number: E123529-101242682

Report Date: 8/9/2012 Last Revised: 9/21/2012